

CFW701 HVAC



Variable Speed Drive

In order to be present in the world's biggest drives market WEG developed a product dedicated to heating, ventilation, air conditioning and refrigeration applications. Beyond a specific hardware designed for this purpose the CFW701 also brings in specific functions to perform according to market needs.

The Full HVAC Potential



Fire Mode

This function makes the drive to inhibit its internal faults making the motor run at adverse conditions without stopping the process.



Sleep / Wake-Up Mode

It prevents the operation of the motor at low speeds for certain amount of time to be previously programmed. Also the instant when the motor has to be restarted can be determined by using the wake-up mode.



Broken Belt

It monitors motor torque and prevents it from running with no load in case of a broken belt.



Energy Saving

Depending on the motor speed and load conditions the flux is reduced decreasing losses and therefore efficiency is improved causing energy saving.



Filter Maintenance Alarm

It warns about the need to replace the filter.



Bypass

Using one of its output relay the CFW701 HVAC allows the motor to be started cross the line. An external circuitry is needed for this operation.



USB Port

Ready to connect with a computer.



Dry Pump

It prevents the pump from running with no load.



PTC

Possibility for monitoring PTC sensor.



Short Cycle Protection

It prevents a compressor/motor from being switched on and off in short period of times.

Motor Power Range

0.18 to 110 kW (0.25 to 150 HP)

Certifications



Characteristics

- **Focus on HVAC Duty**
Overload current: 150% during 60s
Ambient temperature: up to 50 °C
- **RFI Filter Built-In**
RFI Filter complying with IEC 61800-3 Category C3
- **Low Harmonic Distortion**
Meets the standard IEC 61000-3-12
- **SoftPLC**
PLC functions: making it a flexible and optimized solution
- **Advanced PID**
Main PID control the process by itself and 2 additional PID for use to control an independent process
- **Communication Protocols**
BACnet MS/TP, Modbus N2 and Modbus-RTU
- **Conformal Coating as Standard**

Accessories

- **Intuitive HMI**
Built-in as standard and remote for the panel door



Inputs and Outputs (I/O):

- 8 Isolated digital inputs
- 3 Differential analog inputs (0-10 V/4-20 mA (2) and 4-20 mA (1))
- 5 Digital outputs (2 relays with NA contacts, 3 isolated transistors)
- 2 Non-isolated analog outputs
- 1 Dedicated input for PTC



Specific Engineering Units for HVAC for both HMI.



CFW701 HVAC

Variable Speed Drive

Applications

- Hospitals
- Shopping
- Commercial buildings
- Universities
- Schools
- Airports
- Hotels
- Clean rooms
- Pump and fan applications in general



Drive Ratings

CFW701 - variable speed drive						Maximum ND motor power ¹⁾				Maximum HD motor power ¹⁾																		
Power supply (V)		Model	Frame sizes	Normal Duty (ND)	Heavy Duty (HD)	IEC		NEMA		IEC		NEMA																
				A	A																							
Single-phase	200-240	CFW701 A 06P0 S2	A	6	5			1.1		1.5		1.1	1															
		CFW701 A 07P0 S2		7	7									1.5	2	1.5	2											
		CFW701 A 10P0 S2		10	10									2.2	3	2.2	3											
Single-phase or three-phase	200-240	CFW701 A 06P0 B2	A	6	5			1.1		1.5		1.1	1															
		CFW701 A 07P0 B2		7	7									1.5	2	1.5	2											
Three-phase	200-240	CFW701 A 07P0 T2	A	7	5.5	50 Hz - 220 V / 230 V		1.5	60 Hz - 230 V	2	1.1	50 Hz - 220 V / 230 V	1.1	1														
		CFW701 A 10P0 T2		10	8										2.2	3	1.5	2										
		CFW701 A 13P0 T2		13	11										3	3	2.2	3										
		CFW701 A 16P0 T2		16	13										4	5	3	3										
		CFW701 B 24P0 T2	B	24	20										5.5	7.5	5.5	5										
		CFW701 B 28P0 T2		28	24										7.5	10	5.5	7.5										
		CFW701 B 33P0 T2		33.5	28										9.2	10	7.5	10										
		CFW701 C 45P0 T2	C	45	36										11	15	9.2	10										
		CFW701 C 54P0 T2		54	45										15	20	11	15										
		CFW701 C 70P0 T2		70	56										18.5	25	15	20										
		CFW701 D 86P0 T2	D	86	70										22	30	18.5	25										
		CFW701 D 0105P0 T2		105	86										30	40	22	30										
		Three-phase	380-480	CFW701 E 0142P0 T2	E										142	115			37	50	30	40	30	40				
				CFW701 E 0180P0 T2											180	142									55	60	37	50
				CFW701 E 0211P0 T2											211	180									55	75	55	60
Three-phase	380-480	CFW701 A 03P6 T4	A	3.6	3.6	50 Hz - 380 V / 415 V		1.5	60 Hz - 460 V	2	1.5	50 Hz - 380 V / 415 V	1.5	2														
		CFW701 A 05P0 T4		5	5										2.2	3	2.2	3										
		CFW701 A 07P0 T4		7	5.5										3	3	2.2	3										
		CFW701 A 10P0 T4		10	10										4	5	4	5										
		CFW701 A 13P5 T4		13.5	11										5.5	7.5	4	7.5										
		CFW701 B 17P0 T4	B	17	13.5										7.5	10	5.5	7.5										
		CFW701 B 24P0 T4		24	19										11	15	9.2	10										
		CFW701 B 31P0 T4		31	25										15	20	11	15										
		CFW701 C 38P0 T4	C	38	33										18.5	25	15	20										
		CFW701 C 45P0 T4		45	38										22	30	18.5	25										
		CFW701 C 58P5 T4		58.5	47										30	40	22	30										
		CFW701 D 70P5 T4	D	70.5	61										37	50	30	40										
		CFW701 D 88P0 T4		88	73										45	60	37	50										
		CFW701 E 0105 T4		105	88										55	75	45	60										
		CFW701 E 0142 T4	E	142	115										75	100	55	75										
		CFW701 E 0180 T4		180	142										90	150	75	100										
		CFW701 E 0211 T4		211	180										110	150	90	150										
		CFW701 B 02P9 T5		B	2.9										2.7	1.5	2	1.5	2									
		CFW701 B 04P2 T5	4.2		3.8										2.2	3	2.2	2										
		CFW701 B 07P0 T5	7		6.5										4	5	4	5										
		CFW701 B 10P0 T5	10		9										5.5	7.5	5.5	7.5										
CFW701 B 12P0 T5	12	10	7.5		10	5.5	7.5																					
Three-phase	500-600	CFW701 B 17P0 T5	B	17	17	50 Hz - 525 V / 575 V		11	60 Hz - 575 V	15	11	50 Hz - 525 V / 575 V	11	15														
		CFW701 D 22P0 T5		22	19										15	20	11	15										
		CFW701 D 27P0 T5		27	22										18.5	25	15	20										
		CFW701 D 32P0 T5		32	27										22	30	18.5	25										
		CFW701 D 44P0 T5		44	36										30	40	22	30										
		CFW701 E 53P0 T5	D	53	44										37	50	30	40										
		CFW701 E 63P0 T5		63	53										45	60	37	50										
		CFW701 E 80P0 T5		80	66										55	75	45	60										
		CFW701 E 0107 T5		107	90										75	100	55	75										
		CFW701 E 0125 T5		125	107										90	125	75	100										
		CFW701 E 0150 T5	E	150	122										110	150	90	100										

Note: 1) Use motor power ratings above only as a guideline. Motors are rated for 400 V, 50 Hz, 4-pole. The right way to size a VSD is matching its output current with the rated motor current.



Grupo WEG - Automation Business Unit
Jaraguá do Sul - SC - Brazil
Phone: +55 47 3276 4000
automacao@weg.net
www.weg.net